

E-SERIES™ MANURE SPREADER

THE POWERFUL YET AFFORDABLE CHOICE



LENGTH

up to 26 ft

LEVEL CAPACITY

up to 686 ft³

HEAPED CAPACITY

up to 858 ft³

CARRYING CAPACITY

up to 50,000 lbs

EMPTY WEIGHT

up to 21,500 lbs



JBS EQUIPMENT

The field's the limit



QUICK ATTACH
VERTIMAX VERTICAL
BEATERS



HYDRAULIC
GUILLOTINE GATE



LOW MAINTENANCE
HYDRAULIC GEARBOX



UHMW LOW FRICTION,
HARD-WEARING
PLASTIC FLOOR



LONG-LINK 5/8" GRADE
100 FLOOR CHAIN



E-SERIES MANURE SPREADER

MODEL	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
DIMENSIONS							
Overall Length (in)	294	296	319	337	361	385	409
Overall Height (in)	118	118	118	122	122	122	122
Overall Width (in)	135	132	135	135	135	135	135
Inside Box Width (in)	78	78	78	78	78	78	78
Inside Box Length (in)	168	168	192	216	240	264	288
Load Height (in)	76	89	89	91	91	91	91
Level Capacity (ft³)	317	369	421	473	525	577	629
Heaped Capacity (ft³)	425	454	517	581	645	706	769
Carrying Capacity (lbs)	25,000	50,000	50,000	50,000	50,000	50,000	50,000
Empty Weight (lbs)	9000	10,500	12,500	14,500	16,500	18,500	21,500
Box Construction	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge
STANDARD FEATURES							
Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Axle	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
Tire Size	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5	600/50-22.5
Tire Options	Yes	Yes	Yes	Yes	Yes	Yes	Yes
End Gate	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine
Bulkhead	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hitch Type	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Decal Package	Basic	Basic	Basic	Basic	Basic	Basic	Basic
APRON/FLOOR							
Floor Chain	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100	Long-Link 5/8" Grade 100
Galvanized & Removable Cross Slats	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floor Drive	Single	Single	Single	Single	Dual	Dual	Dual
UHMW Plastic Floor	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Sprockets	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings	Steel Idler Sprocket with Bronze Brushings
BEATERS							
Vertimax Vertical Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hurricane Beaters	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Quick Attach Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hardox® Beaters	No	No	No	No	No	No	No
MECHANICAL							
Horse-power (HP) Requirements	110-150	125-150	140-175	160-200	175-225	185-220	200-275
Beater Protection	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt
Hydraulic Brakes	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Steering Axle(s)	No	No	No	No	No	No	No
Rear Drive Shaft Diameter (in)	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16	2 3/16
OPTIONAL UPGRADES							
Silage Kit	No	No	No	No	No	No	No
Wall Extensions	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Scale and Rate Controller Systems	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flight Protection System	Optional	Optional	Optional	Optional	Optional	Optional	Optional

The field's the limit

www.jbsequipment.com