

# LOW-RIDER® SPREADER

A STEP ABOVE THE REST



**LENGTH UP TO**

36 ft

**LEVEL CAPACITY UP TO**

1410 ft<sup>3</sup>

**HEAPED CAPACITY UP TO**

1610 ft<sup>3</sup>

**CARRYING CAPACITY UP TO**

128,000 lbs

**EMPTY WEIGHT UP TO**

41,600 lbs

**SUSPENSION UP TO**

64 Tonne spring



**JBS EQUIPMENT**

The field's the limit



MASSIVE HEAPED CAPACITY



ULTIMATE STABILITY ON  
UNEVEN TERRAIN



TOUGH AND RELIABLE  
750-60R-30.5 TIRES



LOW RIDER MANURE SPREADER

| MODEL                              | VMWB2630-34L             | VMWB3042-48L             | VMWB3042-50L             | VMWB3642-64L             |
|------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| <b>Dimensions</b>                  |                          |                          |                          |                          |
| Overall Length (in)                | 437                      | 486                      | 486                      | 555                      |
| Overall Height (in)                | 143                      | 156                      | 153                      | 156                      |
| Overall Width (in)                 | 161                      | 161                      | 162                      | 161                      |
| Inside Box Width (in)              | 82                       | 82                       | 82                       | 82                       |
| Inside Box Length (in)             | 290                      | 336                      | 336                      | 408                      |
| Load Height (in)                   | 122                      | 132                      | 132                      | 136                      |
| Level Capacity (ft <sup>3</sup> )  | 780                      | 1100                     | 1100                     | 1410                     |
| Heaped Capacity (³)                | 918                      | 1260                     | 1320                     | 1610                     |
| Carrying Capacity (lbs)            | 68,000                   | 96,000                   | 100,000                  | 128,000                  |
| Empty Weight (lbs)                 | 29,700                   | 37,300                   | 35,500                   | 41,600                   |
| Box Construction                   | 10 Gauge                 | 10 Gauge                 | 10 Gauge                 | 10 Gauge                 |
| <b>Standard Features</b>           |                          |                          |                          |                          |
| Suspension                         | Spring                   | Spring                   | Hydraulic                | Spring                   |
| Axle                               | Tandem                   | Tridem                   | Tridem                   | Quad                     |
| Tire Size                          | 750-60R-30.5             | 750-60R-30.5             | 750-60R-30.5             | 750-60R-30.5             |
| Tire Options                       | No                       | No                       | No                       | No                       |
| End Gate                           | Guillotine               | Guillotine               | Guillotine               | Guillotine               |
| Bulkhead                           | Standard                 | Standard                 | Standard                 | Standard                 |
| Hitch Type                         | Standard or Equal Angle  | Standard or Equal Angle  | Standard or Equal Angle  | Equal Angle              |
| Decal Package                      | Premium                  | Premium                  | Premium                  | Premium                  |
| <b>Apron/Floor</b>                 |                          |                          |                          |                          |
| Floor Chain                        | Long-Link 5/8" Grade 100 | Long-Link 5/8" Grade 100 | Long-Link 5/8" Grade 100 | Long-Link 5/8" Grade 100 |
| Galvanized & Removable Cross Slats | Yes                      | Yes                      | Yes                      | Yes                      |
| Floor Drive                        | Dual                     | Dual                     | Dual                     | Dual                     |
| Planetary Drive                    | Yes                      | Yes                      | Yes                      | Yes                      |
| UHMW Plastic Floor                 | Yes                      | Yes                      | Yes                      | Yes                      |
| Sprockets                          | Steel Idler Sprocket     | Steel Idler Sprocket     | Steel Idler Sprocket     | Steel Idler Sprocket     |
| <b>Beaters</b>                     |                          |                          |                          |                          |
| Vertimax Vertical Beaters          | Yes                      | Yes                      | Yes                      | Yes                      |
| Hurricane Compost Attachment       | Optional                 | Optional                 | Optional                 | Optional                 |
| Quick Attach Beaters               | Yes                      | Yes                      | Yes                      | Yes                      |
| Hardox® Lined Beaters              | Optional                 | Optional                 | Optional                 | Optional                 |
| <b>Mechanical</b>                  |                          |                          |                          |                          |
| Beater Protection                  | Shear Bolt               | Shear Bolt               | Shear Bolt               | Shear Bolt               |
| Hydraulic Brakes                   | Yes                      | Yes                      | Yes                      | Yes                      |
| Steering Axle(s)                   | Yes                      | Yes                      | Yes                      | Yes                      |
| Rear Drive Shaft Diameter (in)     | 2 7/16                   | 2 7/16                   | 2 7/16                   | 2 7/16                   |
| <b>Add Ons</b>                     |                          |                          |                          |                          |
| Silage Kit                         | Optional                 | Optional                 | Optional                 | Optional                 |
| Wall Extensions                    | Optional                 | Optional                 | Optional                 | Optional                 |
| Scale and Rate Controller Systems  | Optional                 | Optional                 | Optional                 | Optional                 |
| Flight Protection System           | Optional                 | Optional                 | Optional                 | Optional                 |

The field's the limit

www.jobsequipment.com