

# WIDE BODY MANURE SPREADER

THE RIGHT TECHNOLOGY FOR THE MOST  
EFFICIENT FIELDWORK.



**LENGTH**

up to 34 ft

**LEVEL CAPACITY**

up to 1006 ft<sup>3</sup>

**HEAPED CAPACITY**

up to 1258 ft<sup>3</sup>

**CARRYING CAPACITY**

up to 100,000 lbs

**EMPTY WEIGHT**

up to 32,000 lbs



**JBS EQUIPMENT**

The field's the limit



QUICK ATTACH  
VERTIMAX VERTICAL  
BEATERS



HYDRAULIC  
GUILLOTINE GATE



UHMW LOW FRICTION,  
HARD-WEARING  
PLASTIC FLOOR



LONG-LINK 5/8" GRADE  
100 FLOOR CHAIN



WIDE BODY MANURE SPREADER

MODEL	VMWB2448-23	VMWB2648-34	VMWB3048-36	VMWB3048-48	VMWB3048-50	VMWB3448-48	VMWB3448-50
<b>Dimensions</b>							
Overall Length (in)	413	437	485	534	534	582	582
Overall Height (in)	140	145	146	146	146	167	167
Overall Width (in)	125	125	125	125	125	125	125
Inside Box Width (in)	88	88	88	88	88	88	88
Inside Box Length (in)	264	288	336	336	336	384	384
Load Height (in)	111	117	114	117	119	116	119
Level Capacity (ft <sup>3</sup> )	710	800	888	888	888	1006	1006
Heaped Capacity (ft <sup>3</sup> )	888	975	1110	1110	1110	1258	1258
Carrying Capacity (lbs)	46,000	68,000	72,000	96,000	100,000	96,000	100,000
Empty Weight (lbs)	24,500	27,700	23,500	25,000	26,500	30,500	32,000
Box Construction	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge
<b>Standard Features</b>							
Suspension	Spring	Spring	Spring	Spring	Hydraulic	Spring	Hydraulic
Axle	Tandem	Tandem	Tridem	Tandem	Tridem	Tandem	Tridem
Tire Size	700/40-22.5	750/45R-26.5	700/40-22.5	750/45R-26.5	750/45R-26.5	750/45R-26.5	750/45R-26.5
Tire Options	No	Yes	No	Yes	Yes	No	No
End Gate	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine	Guillotine
Bulkhead	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Hitch Type	Standard or Equal Angle	Standard or Equal Angle	Standard or Equal Angle	Standard or Equal Angle	Standard or Equal Angle	Standard or Equal Angle	Standard or Equal Angle
Decal Package	Premium	Premium	Premium	Premium	Premium	Premium	Premium
<b>Apron/Floor</b>							
Floor Chain Long-Link 5/8" Grade 100	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Galvanized & Removable Cross Slats	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floor Drive	Dual	Dual	Dual	Dual	Dual	Dual	Dual
Planetary Drive	Optional	Optional	Yes	Yes	Yes	Yes	Yes
UHMW Plastic Floor	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Steel Idler Sprocket with Bronze Brushings	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Beaters</b>							
Vertimax Vertical Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hurricane Compost Attachment	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Quick Attach Beaters	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hardox Lined Beaters	Optional	Optional	Optional	Optional	Optional	Optional	Optional
<b>Mechanical</b>							
Beater Protection	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt	Shear Bolt
Hydraulic Brakes	Optional	Optional	Yes	Yes	Yes	Yes	Yes
Steering Axle(s)	Optional	Optional	Yes	Yes	Yes	Yes	Yes
Rear Drive Shaft Diameter (in)	2 3/16	2 3/16	2 3/16	2 7/16	2 7/16	2 7/16	2 7/16
<b>Optional Upgrades</b>							
Silage Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Wall Extensions	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Scale and Rate Controller Systems	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flight Protection System	Optional	Optional	Optional	Optional	Optional	Optional	Optional